

15W47



Color:  Yellow

UPC Code: 07847784824

Country Of Origin: United States

* Eligible for ARRA funded projects

NEMA:
5-15R



Made in USA



15W47

Brand Features

Leviton's Wetguard products are the most versatile and well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

Item Description

15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Connector, Straight Blade, Industrial Grade, Grounding, Wetguard - Yellow

Technical Information

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 Volt

Amperage: 15 Amp

Current Limiting: Full Rated Current

Wire: 3

Pole: 2

Environmental Specifications

Operating Temperature: -40C to 60C

Flammability: Rated V-2 per UL94

Material Specifications

Body Material: EPTR Rubber

Terminal Screws: Electroless Nickel-coated Brass

Wire Module: Nylon

Blades/Contacts: Nickel-Plated Brass

Body Interior: Nylon

Bushing: Santoprene TPV

Compression Nut, Strain Relief: Nylon

Assembly Screws: Stainless Steel 300

Mechanical Specifications

Product ID: Ratings and NEMA I.D. permanently marked on device

Cord Grip Range (in): .234-.687

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 18-10 AWG

Product Features

Body Material: EPTR Rubber

Color: Yellow

Blades/Contacts: Nickel-Plated Brass

NEMA: 5-15R

Assembly Screws: Stainless Steel 300

Standards and Certifications

Warranty: Lifetime Warranty

CSA C22.2 No. 42: File LR-406

UL: 498

ANSI: C-73

NOM: 057

NEMA: WD-6