

27W81



Color: Yellow

UPC Code: 07847796790

Country Of Origin: United States

* Eligible for ARRA funded projects



Made in USA



27W81

Brand Features

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

Item Description

20 Amp, 120/208 Volt 3PY, NEMA L21-20R, 4P, 5W, Locking Connector, Industrial Grade, Grounding, Wetguard - YELLOW

Technical Information

Electrical Specifications

Dielectric Voltage: Withstands 2000V

per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 120/208 Volt 3PY

Amperage: 20 Amp

Current Limiting: Full Rated Current

Wire: 5 Pole: 4

Environmental Specifications

Operating Temperature: -40C to 60C **Flammability:** Rated V-2 per UL94

Material Specifications

Body Material: EPTR Rubber

Terminal Screws: Electroless Nickel-

coated Brass

Wire Module: Nylon

Blades/Contacts: Nickel-Plated Brass

Body Interior: Nylon **Bushing:** Santoprene TPV

Compression Nut, Strain Relief: Nylon Assembly Screws: Stainless Steel 300

Mechanical Specifications

Product ID: Ratings and NEMA I.D. permanently marked on device

Cord Grip Range (in): .375-.875

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: #16 to #10

Product Features

Body Material: EPTR Rubber

Color: Yellow

Blades/Contacts: Nickel-Plated Brass **Standards and Certifications:** UL/CSA

NEMA: L21-20R

Assembly Screws: Stainless Steel 300

Standards and Certifications
Warranty: Lifetime Warranty
CSA C22.2 No. 42: File LR-406

UL: 498 ANSI: C-73 NOM: 057 NEMA: WD-6