# 26W81





UPC Code: 07847796852 Country Of Origin: United States \* Eligible for ARRA funded projects





## 26W81

### Brand Features

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

#### **Item Description**

20 Amp, 120/208 Volt 3PY, NEMA L21-20P, 4P, 5W, Locking Plug, Industrial Grade, Grounding, Wetguard - YELLOW

#### **Technical Information**

**Electrical Specifications** Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current Voltage: 120/208 Volt 3PY

Amperage: 20 Amp Current Limiting: Full Rated Current Wire: 5

Pole: 4

**Environmental Specifications** Operating Temperature: -40C to 60C Flammability: Rated V-2 per UL94

#### Material Specifications

Body Material: EPTR Rubber Terminal Screws: Electroless Nickelcoated Brass Wire Module: Nylon Blades/Contacts: Nickel-Plated Brass

Body Interior: Nylon

Bushing: Santoprene TPV

Compression Nut, Strain Relief: Nylon Assembly Screws: Stainless Steel 300

**Mechanical Specifications** 

Product ID: Ratings and NEMA I.D. permanently marked on device

Cord Grip Range (in): .375-.875 Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral Terminal Accom.: #16 to #10

**Product Features** Body Material: EPTR Rubber Color: Yellow Blades/Contacts: Nickel-Plated Brass

Standards and Certifications: UL/CSA NEMA: L21-20P Assembly Screws: Stainless Steel 300

Standards and Certifications Warranty: Lifetime Warranty CSA C22.2 No. 42: File LR-406 UL: 498 ANSI: C-73 NOM: 057 NEMA: WD-6

