

# 29W81





UPC Code: 07847796882
Country Of Origin: United States
\* Eligible for ARRA funded projects

**NEMA:** L21-30R



Made in USA



# 29W81

### **Brand Features**

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

### **Item Description**

30 Amp, 120/208 Volt 3PY, NEMA L21-30R, 4P, 5W, Locking Connector, Industrial Grade, Grounding, Wetguard - YELLOW

#### **Technical Information**

**Electrical Specifications** 

**Dielectric Voltage:** Withstands 2000V

per UL498

**Grounding:** Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 120/208 Volt 3PY

Amperage: 30 Amp

**Current Limiting:** Full Rated Current

Wire: 5 Pole: 4

**Environmental Specifications** 

**Operating Temperature:** -40C to 60C **Flammability:** Rated V-2 per UL94

Material Specifications

Body Material: EPTR Rubber

Terminal Screws: Electroless Nickel-

coated Brass

Wire Module: Nylon

Blades/Contacts: Nickel-Plated Brass

**Body Interior:** Nylon **Bushing:** Santoprene TPV

Compression Nut, Strain Relief: Nylon Assembly Screws: Stainless Steel 300

Mechanical Specifications

Product ID: Ratings and NEMA I.D. permanently marked on device

Cord Grip Range (in): .625-1.125

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: #12 to #8

**Product Features** 

Body Material: EPTR Rubber

Color: Yellow

**Blades/Contacts:** Nickel-Plated Brass **Standards and Certifications:** UL/CSA

**NEMA:** L21-30R

Assembly Screws: Stainless Steel 300

Standards and Certifications
Warranty: Lifetime Warranty
CSA C22.2 No. 42: File LR-406

UL: 498 ANSI: C-73 NOM: 057 NEMA: WD-6