

28W81



UPC Code: 07847796905

Country Of Origin: United States

* Eligible for ARRA funded projects

NEMA:
L21-30P



Made in USA



28W81

Brand Features

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

Item Description

30 Amp, 120/208 Volt 3PY, NEMA L21-30P, 4P, 5W, Locking Plug, Industrial Grade, Grounding, Wetguard - YELLOW

Technical Information

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 120/208 Volt 3PY

Amperage: 30 Amp

Current Limiting: Full Rated Current

Wire: 5

Pole: 4

Environmental Specifications

Operating Temperature: -40C to 60C

Flammability: Rated V-2 per UL94

Material Specifications

Body Material: EPTR Rubber

Terminal Screws: Electroless Nickel-coated Brass

Wire Module: Nylon

Blades/Contacts: Nickel-Plated Brass

Body Interior: Nylon

Bushing: Santoprene TPV

Compression Nut, Strain Relief: Nylon

Assembly Screws: Stainless Steel 300

Mechanical Specifications

Product ID: Ratings and NEMA I.D. permanently marked on device

Cord Grip Range (in): .625-1.125

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: #12 to #8

Product Features

Body Material: EPTR Rubber

Color: Yellow

Blades/Contacts: Nickel-Plated Brass

Standards and Certifications: UL/CSA

NEMA: L21-30P

Assembly Screws: Stainless Steel 300

Standards and Certifications

Warranty: Lifetime Warranty

CSA C22.2 No. 42: File LR-406

UL: 498

ANSI: C-73

NOM: 057

NEMA: WD-6