

CS6364C



UPC Code: 07847732621

Country Of Origin: Mexico

**Eligible for ARRA funded projects > \$7,443,000*

NEMA:
Non-NEMA



CS6364C

Brand Features

Leviton's Black &White 50 Amp, Non-NEMA line of industrial grade locking blade devices feature rugged construction that resists impact, sunlight, chemicals and rough use. All contacts and blades are solid one-piece construction for superior conductivity. Corrosion resistant versions feature nickel plated contacts and blades, plus stainless steel shrouds and screws. The ergonomic, fluted-body design with radial gripping edge is ideal for gripping and pulling. The unique cord clamp accepts a wide range of cord sizes, providing a secure grip without damaging the cord. And, they are backed by a limited lifetime warranty.

Item Description

50Amp, 125/250V AC, Non-NEMA, 3P, 4W, Black &White Locking Connector, Industrial Grade, Grounding, California-Style(CS) – BLACK-WHITE

Technical Information

Electrical Specifications

Dielectric Voltage Withstand: 2000V minimum per UL 498

Grounding: Grounding

Temperature Rise: Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

Maximum Working Voltage: 125/250V as rated

Voltage: 125/250 Volt

Current Interrupting: Certified for current interrupting at full rated current

Amperage: 50 Amp

Wire: 4

Pole: 3

Environmental Specifications

Operating Temperature: -40deg.C to 75deg.C (-40deg.F to 167deg.F)

Flammability: Rated HB or better UL94

Material Specifications

Terminal Set Screw: SS 302/304

Ground Shunt: Bronze

Wiring Chamber: Nylon

Housing Material: Nylon

Cable Clamp Screw: Philips Head, SS 304

Color: Black-White

Contact - Binding Plate: 0.100inch thick Brass

Ground Post: Brass

Contact Rivet: Brass

Face Module: Nylon

Contact - Spring Value: 0.041inch thick Brass

Terminal Block: 0.062inch thick Copper

Center Pin: SS 302/304

Standard Cable Clamp: Nylon

Dust Shield: Santoprene TPE

Assembly Screws: Brass

Mechanical Specifications

Product ID: Ratings and Catalogue No. molded into face and stamped into shroud

Terminal ID: X, W, Y, Z and Green for ground

Terminal Accom.: #10 min to #4max AWG Solid or Stranded Wire

Cord Range: .680 - 1.125

Product Features

Color: Black-White

NEMA: Non-NEMA

Standards and Certifications

UL 498: File E13399

Warranty: Lifetime Limited

CSA C22.2 No. 42: File 152105

NOM: 057

RoHS: Compliant

