



4/0 1/C (UL) TYPE W CLASS K

CONDUCTOR:	4/0 2090W CLASS K BARE COPPER.	<u>TYPICAL</u> OD: 0.579"
SEPARATOR:	SUITABLE TAPE.	
INSULATION:	0.080" (MIN. AVG.) OF ETHYLENE PROPYLENE RUBBER (EPR).	OD: 0.760"
REINFORCEMENT:	TWO REVERSE / OPEN WRAPS OF COTTON FILAMENT	
JACKET:	0.095" (MIN. AVG.) OF BLACK HEAVY DUTY CHLORINATED POLYETHYLENE (CPE).	OD: 0.956"
CABLE LEGEND:	AMERCABLE (UL) TYPE W 4/0 AWG 1/C 90C WET OR DRY 2000V SUN RES OIL RESISTANT 60C -40C CSA LR 82346 FT1 FT5 07-KA160015 MSHA	
APPX WEIGHT:	965 POUNDS PER 1000 FEET	
VOLTAGE RATING:	2000V	



THIS DRAWING AND SET OF PLANS, AND ALL INFORMATION AND SPECIFICATIONS SET FORTH HEREON, IS THE COPYRIGHTED AND CONFIDENTIAL EXCLUSIVE PROPERTY OF NEXANS AMERC/ BLE. ANY USE FOR ANY PURPOSE WHATSOEVER, INCLUDING WITHOUT LIMITATION COPYING OR DISTRIBUTION, WITHOUT THE EXPRESS WRITTEN PERMISSION OF NEXANS AMERCABLE IS EXPRESSLY PROHIBITED. THIS DRAWING MUST BE RETURNED ON DEMAND BY NEXANS AMERCABLE.

REV	DATE	CHANGE	DRAWN BY Tim Avant	DATE 04/16/18
DIMENSIONAL TOLERANCE +/- 5%		SCALE NTS	ENGINEERING APPROVAL Kevin Hebert	DATE 04/16/18
DRAWING NUMBER 37401040A		REV 0	CUSTOMER APPROVAL	DATE