

## 5269-CB



Color:  Black

UPC Code: 07847782526

Country Of Origin: United States

\* Eligible for ARRA funded projects

NEMA:  
5-15R



Made in USA



## 5269-CB

### Brand Features

The Leviton line of Straight Blade Plugs and Connectors includes: Black & White® Industrial Grade devices that resist impact, corrosion and chemicals; Wetguard® for water or moisture resistance; Dustgard® for dust and dirt; Python™, with an innovative interlocking design; rugged nylon flanged and outlets; and integrated inlets and outlets with weather resistant covers.

### Item Description

15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Connector, Straight Blade, Industrial Grade, Grounding - Black

### Technical Information

#### Electrical Specifications

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Grounding

**Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage:** 125 Volt

**Current Interrupting:** Certified for current interrupting at full rated current

**Amperage:** 15 Amp

**Wire:** 3

**Pole:** 2

#### Environmental Specifications

**Operating Temperature:** -40C to 60C

**Flammability:** Rated HB or better UL94

#### Material Specifications

**Body Material:** Impact Modified Nylon

**Back Cover:** Thermoplastic

**Terminal Screws:** Brass

**Wire Module:** Nylon

**Color:** Black

**Cord-Clamp:** Nylon

**Blades/Contacts:** Solid Brass

**Clamp Insert:** Nylon

**Assembly Screws:** Steel, Zinc Plated

#### Mechanical Specifications

**Product ID:** Ratings and NEMA I.D. permanently marked on device

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

**Terminal Accom.:** 18-10 AWG

**Cord Range:** .245 - .700

#### Product Features

**Color:** Black

**NEMA:** 5-15R

#### Standards and Certifications

**UL 498:** File E13399

**Warranty:** Lifetime Warranty

**CSA C22.2 No. 42:** File LR-406

**UL Fed Spec WC-596:** File E13393

**ANSI:** C-73

**NOM:** 057

**NEMA:** WD-6

# 2513



UPC Code: 07847705689

Country Of Origin: United States

\* Eligible for ARRA funded projects

NEMA:  
L21-20R



Made in USA



# 2513

## Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

## Item Description

20 Amp, 120/208 Volt 3PY, NEMA L21-20R, 4P, 5W, Locking Connector, Industrial Grade, Grounding - BLACK-WHITE

## Technical Information

### AC Horsepower Ratings

**At Rated Voltage:** 2 HP

### Electrical Specifications

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Grounding

**Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage:** 120/208 Volt 3PY

**Current Interrupting:** Certified for current interrupting at full rated current

**Amperage:** 20 Amp

**Wire:** 5

**Pole:** 4

### Environmental Specifications

**Operating Temperature:** -40C to 60C

**Flammability:** Rated HB or better UL94

### Material Specifications

**Body Material:** Impact Modified Nylon

**Back Cover:** Thermoplastic

**Terminal Screws:** Brass

**Wire Module:** Nylon

**Color:** Black-White

**Cord-Clamp:** Nylon

**Blades/Contacts:** Solid Brass

**Clamp Insert:** Nylon

**Assembly Screws:** Steel, Zinc Plated

### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

**Terminal Accom.:** 18-10 AWG

**Cord Range:** .595 - .895

**Wire Gauge:** 14-10 AWG

### Product Features

**Color:** Black-White

**NEMA:** L21-20R

### Standards and Certifications

**Warranty:** Lifetime Warranty

**CSA C22.2 No. 42:** File LR-406

**UL Fed Spec WC-596:** File E13393

**ANSI:** C-73

**UL498:** File E13393

**NOM:** 057

**NEMA:** WD-6

2813



UPC Code: 07847780860

Country Of Origin: United States

\* Eligible for ARRA funded projects

NEMA:  
L21-30R



Made in USA



2813

#### Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

#### Item Description

30 Amp, 120/208 Volt 3PY, NEMA L21-30R, 4P, 5W, Locking Connector, Industrial Grade, Grounding - BLACK-WHITE

#### Technical Information

##### AC Horsepower Ratings

**At Rated Voltage:** 3 HP

##### Electrical Specifications

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Grounding

**Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage:** 120/208 Volt 3PY

**Current Interrupting:** Certified for current interrupting at full rated current

**Amperage:** 30 Amp

**Wire:** 5

**Pole:** 4

##### Environmental Specifications

**Operating Temperature:** -40C to 60C

**Flammability:** Rated HB or better UL94

##### Material Specifications

**Body Material:** Impact Modified Nylon

**Back Cover:** Thermoplastic

**Terminal Screws:** Brass

**Wire Module:** Nylon

**Color:** Black-White

**Cord-Clamp:** Nylon

**Blades/Contacts:** Solid Brass

**Clamp Insert:** Nylon

**Assembly Screws:** Steel, Zinc Plated

##### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

**Terminal Accom.:** 18-10 AWG

**Cord Range:** .595 - 1.150

**Wire Gauge:** 14-8 AWG

##### Product Features

**Color:** Black-White

**NEMA:** L21-30R

##### Standards and Certifications

**Warranty:** Lifetime Warranty

**CSA C22.2 No. 42:** File LR-406

**UL Fed Spec WC-596:** File E13393

**ANSI:** C-73

**UL498:** File E13393

**NOM:** 057

**NEMA:** WD-6

## 2413-B



Color:  Black

UPC Code: 07847714350

Country Of Origin: United States

\* Eligible for ARRA funded projects

NEMA:  
L14-20R



Made in USA



## 2413-B

### Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

### Item Description

20 Amp, 125/250 Volt, NEMA L14-20R, 3P, 4W, Locking Connector, Industrial Grade, Grounding - BLACK

### Technical Information

#### AC Horsepower Ratings

**At Rated Voltage:** 2 HP L-L / 1 HP L-N

#### Electrical Specifications

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Grounding

**Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage:** 125/250 Volt

**Current Interrupting:** Certified for current interrupting at full rated current

**Amperage:** 20 Amp

**Wire:** 4

**Pole:** 3

#### Environmental Specifications

**Operating Temperature:** -40C to 60C

**Flammability:** Rated V-2 per UL94

#### Material Specifications

**Body Material:** Super Tough Nylon

**Back Cover:** Thermoplastic

**Terminal Screws:** Brass

**Wire Module:** Nylon

**Color:** Black

**Cord-Clamp:** Nylon

**Blades/Contacts:** Solid Brass

**Clamp Insert:** Nylon

**Assembly Screws:** Steel, Zinc Plated

#### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

**Terminal Accom.:** 18-10 AWG

**Cord Range:** .595 - .895

**Wire Gauge:** 14-10 AWG

#### Product Features

**Color:** Black

**NEMA:** L14-20R

#### Standards and Certifications

**Warranty:** Lifetime Warranty

**CSA C22.2 No. 42:** File LR-406

**UL Fed Spec WC-596:** File E13393

**ANSI:** C-73

**UL498:** File E13393

**NOM:** 057

**NEMA:** WD-6

## 2313-B



Color:  Black

UPC Code: 07847782788

Country Of Origin: United States

\* Eligible for ARRA funded projects

NEMA:  
L5-20R



Made in USA



## 2313-B

### Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

### Item Description

20 Amp, 125 Volt, NEMA L5-20R, 2P, 3W, Locking Connector, Industrial Grade, Grounding - BLACK

### Technical Information

#### AC Horsepower Ratings

**Horsepower Rating:** 1 HP

#### Electrical Specifications

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Grounding

**Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage:** 125 Volt

**Current Interrupting:** Certified for current interrupting at full rated current

**Amperage:** 20 Amp

**Wire:** 3

**Pole:** 2

#### Environmental Specifications

**Operating Temperature:** -40C to 60C

**Flammability:** Rated HB or better UL94

#### Material Specifications

**Body Material:** Impact Modified Nylon

**Back Cover:** Thermoplastic

**Terminal Screws:** Brass

**Wire Module:** Nylon

**Color:** Black

**Cord-Clamp:** Nylon

**Blades/Contacts:** Solid Brass

**Clamp Insert:** Nylon

**Assembly Screws:** Steel, Zinc Plated

#### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

**Terminal Accom.:** 18-10 AWG

**Cord Range:** .385 - .780

**Wire Gauge:** 16-10 AWG

#### Product Features

**Color:** Black

**NEMA:** L5-20R

#### Standards and Certifications

**Warranty:** Lifetime Warranty

**CSA C22.2 No. 42:** File LR-406

**UL Fed Spec WC-596:** File E13393

**ANSI:** C-73

**UL498:** File E13393

**NOM:** 057

**NEMA:** WD-6

## 2323-B



Color:  Black

UPC Code: 07847784752

Country Of Origin: United States

\* Eligible for ARRA funded projects

NEMA:  
L6-20R



Made in USA



## 2323-B

### Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

### Item Description

20 Amp, 250 Volt, NEMA L6-20R, 2P, 3W, Locking Connector, Industrial Grade, Grounding - BLACK

### Technical Information

#### AC Horsepower Ratings

**Horsepower Rating:** 2 HP

#### Electrical Specifications

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Grounding

**Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage:** 250 Volt

**Current Interrupting:** Certified for current interrupting at full rated current

**Amperage:** 20 Amp

**Wire:** 3

**Pole:** 2

#### Environmental Specifications

**Operating Temperature:** -40C to 60C

**Flammability:** Rated HB or better UL94

#### Material Specifications

**Body Material:** Impact Modified Nylon

**Back Cover:** Thermoplastic

**Terminal Screws:** Brass

**Wire Module:** Nylon

**Color:** Black

**Cord-Clamp:** Nylon

**Blades/Contacts:** Solid Brass

**Clamp Insert:** Nylon

**Assembly Screws:** Steel, Zinc Plated

#### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

**Terminal Accom.:** 18-10 AWG

**Cord Range:** .385 - .780

**Wire Gauge:** 16-10 AWG

#### Product Features

**Color:** Black

**NEMA:** L6-20R

#### Standards and Certifications

**Warranty:** Lifetime Warranty

**CSA C22.2 No. 42:** File LR-406

**UL Fed Spec WC-596:** File E13393

**ANSI:** C-73

**UL498:** File E13393

**NOM:** 057

**NEMA:** WD-6