

5266-CB



Color:  Black

UPC Code: 07847782525

Country Of Origin: United States

* Eligible for ARRA funded projects

NEMA:
5-15P



Made in USA



5266-CB

Brand Features

Leviton's Black & White line of industrial grade plugs and connectors offer superior performance, long-lasting reliability and features that are backed by a lifetime warranty. Available in many NEMA and non-NEMA configurations, you'll be sure to find the right device for your needs.

Item Description

15 Amp, 125 Volt, NEMA 5-15P, 2P, 3W, Plug, Straight Blade, Industrial Grade, Grounding, - Black

Technical Information

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 Volt

Current Interrupting: Certified for current interrupting at full rated current

Amperage: 15 Amp

Wire: 3

Pole: 2

Environmental Specifications

Operating Temperature: -40C to 60C

Flammability: Rated HB or better UL94

Material Specifications

Body Material: Impact Modified Nylon

Back Cover: Thermoplastic

Terminal Screws: Brass

Wire Module: Nylon

Cord-Clamp: Nylon

Blades/Contacts: Solid Brass

Clamp Insert: Nylon

Assembly Screws: Steel, Zinc Plated

Mechanical Specifications

Product ID: Ratings and NEMA I.D. permanently marked on device

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 18-10 AWG

Cord Range: .245 - .700

Product Features

Color: Black

NEMA: 5-15P

Standards and Certifications

UL 498: File E13399

Warranty: Lifetime Warranty

CSA C22.2 No. 42: File LR-406

UL Fed Spec WC-596: File E13393

ANSI: C-73

NOM: 057

NEMA: WD-6

2321-B



Color:  Black

UPC Code: 07847784751

Country Of Origin: United States

* Eligible for ARRA funded projects

NEMA:
L6-20P



Made in USA



2321-B

Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

Item Description

20 Amp, 250 Volt, NEMA L6-20P, 2P, 3W, Locking Plug, Industrial Grade, Grounding - BLACK

Technical Information

AC Horsepower Ratings

Horsepower Rating: 2 HP

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 250 Volt

Current Interrupting: Certified for current interrupting at full rated current

Amperage: 20 Amp

Wire: 3

Pole: 2

Environmental Specifications

Operating Temperature: -40C to 60C

Flammability: Rated HB or better UL94

Material Specifications

Body Material: Impact Modified Nylon

Back Cover: Thermoplastic

Terminal Screws: Brass

Wire Module: Nylon

Color: Black

Cord-Clamp: Nylon

Blades/Contacts: Solid Brass

Clamp Insert: Nylon

Assembly Screws: Steel, Zinc Plated

Mechanical Specifications

Product ID: Ratings are permanently marked on device

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 18-10 AWG

Cord Range: .385 - .780

Wire Gauge: 16-10 AWG

Product Features

Color: Black

NEMA: L6-20P

Standards and Certifications

Warranty: Lifetime Warranty

CSA C22.2 No. 42: File LR-406

UL Fed Spec WC-596: File E13393

ANSI: C-73

UL498: File E13393

NOM: 057

NEMA: WD-6

2311-B



Color:  Black

UPC Code: 07847782787

Country Of Origin: United States

* Eligible for ARRA funded projects

NEMA:
L5-20P



Made in USA



2311-B

Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

Item Description

20 Amp, 125 Volt, NEMA L5-20P, 2P, 3W, Locking Plug, Industrial Grade, Grounding - BLACK

Technical Information

AC Horsepower Ratings

Horsepower Rating: 1 HP

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 Volt

Current Interrupting: Certified for current interrupting at full rated current

Amperage: 20 Amp

Wire: 3

Pole: 2

Environmental Specifications

Operating Temperature: -40C to 60C

Flammability: Rated HB or better UL94

Material Specifications

Body Material: Impact Modified Nylon

Back Cover: Thermoplastic

Terminal Screws: Brass

Wire Module: Nylon

Color: Black

Cord-Clamp: Nylon

Blades/Contacts: Solid Brass

Clamp Insert: Nylon

Assembly Screws: Steel, Zinc Plated

Mechanical Specifications

Product ID: Ratings are permanently marked on device

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 18-10 AWG

Cord Range: .385 - .780

Wire Gauge: 16-10 AWG

Product Features

Color: Black

NEMA: L5-20P

Standards and Certifications

Warranty: Lifetime Warranty

CSA C22.2 No. 42: File LR-406

UL Fed Spec WC-596: File E13393

ANSI: C-73

UL498: File E13393

NOM: 057

NEMA: WD-6

2811



UPC Code: 07847780857

Country Of Origin: United States

* Eligible for ARRA funded projects

NEMA:
L21-30P



Made in USA



2811

Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

Item Description

30 Amp, 120/208 Volt 3PY, NEMA L21-30P, 4P, 5W, Locking Plug, Industrial Grade, Grounding - BLACK-WHITE

Technical Information

AC Horsepower Ratings

At Rated Voltage: 3 HP

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 120/208 Volt 3PY

Current Interrupting: Certified for current interrupting at full rated current

Amperage: 30 Amp

Wire: 5

Pole: 4

Environmental Specifications

Operating Temperature: -40C to 60C

Flammability: Rated HB or better UL94

Material Specifications

Body Material: Impact Modified Nylon

Back Cover: Thermoplastic

Terminal Screws: Brass

Wire Module: Nylon

Color: Black-White

Cord-Clamp: Nylon

Blades/Contacts: Solid Brass

Clamp Insert: Nylon

Assembly Screws: Steel, Zinc Plated

Mechanical Specifications

Product ID: Ratings are permanently marked on device

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 18-10 AWG

Cord Range: .595 - 1.150

Wire Gauge: 14-8 AWG

Product Features

Color: Black-White

NEMA: L21-30P

Standards and Certifications

Warranty: Lifetime Warranty

CSA C22.2 No. 42: File LR-406

UL Fed Spec WC-596: File E13393

ANSI: C-73

UL498: File E13393

NOM: 057

NEMA: WD-6

2511



UPC Code: 07847780851

Country Of Origin: United States

* Eligible for ARRA funded projects

NEMA:
L21-20P



Made in USA



2511

Brand Features

Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

Item Description

20 Amp, 120/208 Volt 3PY, NEMA L21-20P, 4P, 5W, Locking Plug, Industrial Grade, Grounding - BLACK-WHITE

Technical Information

AC Horsepower Ratings

At Rated Voltage: 2 HP

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 120/208 Volt 3PY

Current Interrupting: Certified for current interrupting at full rated current

Amperage: 20 Amp

Wire: 5

Pole: 4

Environmental Specifications

Operating Temperature: -40C to 60C

Flammability: Rated HB or better UL94

Material Specifications

Body Material: Impact Modified Nylon

Back Cover: Thermoplastic

Terminal Screws: Brass

Wire Module: Nylon

Color: Black-White

Cord-Clamp: Nylon

Blades/Contacts: Solid Brass

Clamp Insert: Nylon

Assembly Screws: Steel, Zinc Plated

Mechanical Specifications

Product ID: Ratings are permanently marked on device

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 18-10 AWG

Cord Range: .595 - .895

Wire Gauge: 14-10 AWG

Product Features

Color: Black-White

NEMA: L21-20P

Standards and Certifications

Warranty: Lifetime Warranty

CSA C22.2 No. 42: File LR-406

UL Fed Spec WC-596: File E13393

ANSI: C-73

UL498: File E13393

NOM: 057

NEMA: WD-6

2411-B



Color:  Black

UPC Code: 07847714292

NEMA:
L14-20P



2411-B

Item Description

20 Amp, 125/250 Volt, NEMA L14-20P, 3P, 4W, Locking Plug, Industrial Grade, Grounding, All Black - BLACK

Technical Information

Product Features

Grounding: Grounding

Warranty: Lifetime Warranty

Color: Black

Wire: 4

Feature: All Black

Wire Gauge: 14-10 AWG

NEMA: L14-20P

Body Material: Super Tough Nylon

Voltage: 125/250 Volt

Amperage: 20 Amp

Blades/Contacts: Solid Brass

Standards and Certifications: UL/CSA

Cord Range: .595 - .895

Pole: 3

Assembly Screws: Steel, Zinc Plated

Features and Benefits

- For fast assembly, Black & White devices feature:
- Backed-out, color-coded brass terminal screws
- Deep slotted triple drive face module and cord clamp screws
- Deep wire wells with transparent wiring chambers
- Nylon face module features Amperage, Voltage, and NEMA configuration molded into face for easy identification and replacement.
- Fluted nylon housing makes it easier to grip with gloves and in debris-laden environments
- Thick-walled, super tough nylon housing resists abuse and impact
- Single piece external cord clamp includes catalogue number and NEMA configuration for easy identification
- External cord clamp accepts wire mesh connection grips
- Plugs ship with standard white and black cord clamp. Color-coded cord clamps available to identify amperage or equipment. Choose from blue, green, yellow, red, and orange.